



USE PARALLEL UNITS TO INCREASE VOLUMES IF REQUIRED

Model	823	828	830	1030	1035	1235	1845	2245 ⁽¹⁾	2270 ⁽¹⁾	
Δ p	225	350	375	230	310	210	155	100	250	psi
Max Discharge	740		400					740		psi
Max HP	15	15	30	30	50	50	75 ⁽²⁾	75 ⁽²⁾	125 ⁽²⁾	hp
Max Discharge Temp	392			302						°F
	Max Gas Volumes									
Intake @ 100 psi	199.2	132.5	216.5	351.5	351.5	516.4	1181.2	1660.2	960.8	Mscf/d
Intake @ 75 psi	155.4	103.5	169.5	275.5	275.5	406.2	929.0	1292.8	752.4	Mscf/d
Intake @ 50 psi	112.3	74.2	122.2	198.5	198.5	291.8	666.9	929.0	544.0	Mscf/d
Intake @ 25 psi	68.5	45.6	74.9	121.5	121.5	178.4	408.3	561.6	333.8	Mscf/d
Intake @ 10 psi	42.7	28.3	46.6	75.6	75.6	111.3	254.3	339.1	206.6	Mscf/d
Intake @ 5 psi	33.9	22.6	37.1	60.0	60.0	88.3	201.7	264.9	164.6	Mscf/d
Intake @ 0 psi (3)	25.4	16.8	27.6	44.9	44.9	65.7	162.5	190.7	208.4	Mscf/d

(1) Volumes may be higher with wet gas.

(2) May derate on speed at max HP if the unit exceeds max discharge temperature

(3) 0 psi will depend on adequate supply volume