EGAS Stand Alone Casing Gas Compressors





USE PARALLEL UNITS TO INCREASE VOLUMES IF REQUIRED

Model	823	828	830	1030	1035	1235	1845	2270
∆p	225	350	375	230	310	210	155	250
	1551	2413	2586	1586	2137	1448	1069	1723
Max Discharge /	740		400 740					
MAWP	5102		2758 5102					
Max HP	15	15	30	30	50	50	75(1)	125(1)
Max Discharge Temp	200 150							
-	Max Gas Volumes							
Intake @ 100 psi	5.64	3.75	6.13	9.95	9.95	14.62	33.44	27.2(2)
Intake @ 75 psi	4.40	2.93	4.80	7.80	7.80	11.50	26.30	21.3(2)
Intake @ 50 psi	3.18	2.10	3.46	5.62	5.62	8.26	18.88	15.4(2)
Intake @ 25 psi	1.94	1.29	2.12	3.44	3.44	5.05	11.56	9.45(2)
Intake @ 10 psi	1.21	0.80	1.32	2.14	2.14	3.15	7.20	5.85(2)
Intake @ 5 psi	0.96	0.64	1.05	1.70	1.70	2.50	5.71	4.66(2)
Lub Contra	0.70	0.40	0.79	1 27	1 27	1.86	4.60	E 00(m)

(1) May derate on speed at max HP if the unit exceeds max discharge temperature

(2) Volumes may be higher with wet gas.

(3) 0 psi will depend on adequate supply volume